


TT760P/TT764



Labels for Life.



Over-lamine: 3 mil topcoated gloss clear polyester film that offers excellent resistance to solvents and scratching. Specifically designed to be used as an over-lamine only.

Face Stock: 3 mil topcoated gloss clear polyester film that offers excellent resistance to solvents and scratching. Specifically designed to be used as an over-lamine only.

Adhesive: 0.7 mil high performance permanent acrylic adhesive designed to offer excellent resistance to solvents and scratching.

Release Liner: 1.2 mil clear polyester release liner.

Gloss White Composite Film

TT760P/TT764 is designed for on demand and UV flexographic printing of variable information. Key features include: indoor and outdoor applications, will not shrink and excellent chemical, smudge and abrasion resistance. When used in combination with the recommended IDENTCO ribbon, it will meet the most demanding durable labeling requirements. Preheating of the label surface will enhance the performance.

Typical Applications

- Name Plates
- Rating Plates
- Industrial Barcodes
- Property Identification
- Serial Identification
- Electronic Components Marking

Typical Industry Sectors

- Automotive
- Electronics
- Industrial




www.identco.com


TT760P/TT764

Gloss White Composite Film




Labels for Life.

 **Agency Recognitions**
UL-MH16873


 **Adhesion (TT760P Only)**


Stainless Steel	87 oz/in	957 N/m	HD Polypropylene	42 oz/in	462 N/m
Acrylic Power Paint	89 oz/in	979 N/m	Polycarbonate	99 oz/in	1089 N/m
Polypropylene	36 oz/in	396 N/m	Epoxy Power Paint	111 oz/in	1221 N/m
			Polyester Powder Paint	47 oz/in	517 N/m


 **Material Caliper**


Over-laminate	.0030"	76.2μ	Liner (kraft/FL)	.0012"	30.5μ
Face Stock	.0030"	76.2μ	Total Material	.0079"	200.7μ
Adhesive	.0007"	17.8μ			


 **Exterior Durability**
Material Only: 2 Years
Material w/ TTRR-D Ribbon: 2 Years

 **Temperature Range**
Service Temperature: -40 °F to 302 °F (-40 °C to 150 °C)
Minimum Application Temperature: 50 °F (10 °C)

 **Shelf Life**
Recommended Storage: 45-90 °F (7-32 °C) 20-75% R.H.
Shelf Life: 2 years @ recommended storage

 **Recommended Printing**
Resin Ribbon

 **Chemical Resistance**
Testing can be completed upon request. Testing in actual application is recommended.

 **Process Durability**
It is recommended that customers test the material in actual application to determine if the material meets all requirements.

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 11/1/2016

UNITED STATES HEADQUARTERS

28164 W. Concrete Drive
Ingleside, IL 60041
Phone: +1 (815) 385 - 0011
Fax +1 (815) 385 - 0359

MEXICO MONTERREY

Carr. a Laredo Km. 16.5 Interior
14B, Col. Moisés Sáenz, 66613
Apodaca, Nuevo Leon
Phone: +52 (81) 8008 - 0438

GERMANY FRANKFURT

Güterbahnhofstrasse 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

PRC HONG KONG

Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019

MALAYSIA PENANG

Suite 163E, Level 16, Room 1602
Hunza Tower Gurney Paragon
Jalan Kelawei, Georgetown
10250 Penang
Phone: +6012 466 - 0866