


L5001



Labels for Life.



Film: 5 mil velvet polycarbonate overlaminating film designed to give a finished or Lexan look to a pre-printed label.

Adhesive: 1.2-1.3 mil aggressive, semi-heavy-coat-weight permanent acrylic adhesive.

Liner: 1 mil clear polyester release liner.

Velvet Polycarbonate Overlaminating Film

L5001 is designed to be used to overlaminate another material, giving a finished or Lexan look to a pre-printed label. Key features include: velvet finish, smudge resistance, firmness and thickness that provide protection to base material and rigidity to finished pre-printed label. When used in combination with the recommended IDENTCO materials it will meet the most demanding durable labeling requirements.

Typical Applications

- Overlamine
- Rating plates
- Nameplates
- Pre-printed labels in applications requiring durability

Typical Industry Sectors

- Automotive
- Electronics
- Industrial



www.identco.com

L5001

Velvet Polycarbonate Overlaminating Film



Labels for Life.



Agency Recognitions

RoHS Directive 2002/95/EC Compliant



Adhesion

After 72-hour dwell

Stainless Steel	61 oz/in	671 n/m
Acrylic	68 oz/in	748 n/m



Material Caliper

Film	.0050"	125 μ	Liner (poly)	.0010"	25.4 μ
Adhesive	.0012-.0013"	30.5-33.0 μ	Total Material	.0072-.0073"	180.9-183.4 μ



Exterior Durability

Indoor use only.



Temperature Range

Service Temperature: -40 °F to 212 °F (-40 °C to 100 °C)
Minimum Application Temperature: 50 °F (10 °C)



Shelf Life

Recommended Storage: 45-90 °F (7-32 °C) 20-75%R.H.
Shelf Life: 2 years @ recommended storage



Recommended Printing

Non-printable



Process Durability

It is recommended that customers test the material in actual application to determine if the material meets all requirements.

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 07/03/18

UNITED STATES HEADQUARTERS

28164 W. Concrete Drive,
Ingleside, IL 60041 USA
Phone: +1 (815) 385 - 0011
Fax + (815) 385 - 0359

MEXICO MONTERREY

Carretera a Laredo KM 16.5
Interior 14B Col. Moises Saenz
Apodaca, Nuevo Leon CP 66613
Phone: +51 (81) 8008 - 0438

EUROPE GERMANY

Güterbahnhofstraße 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

ASIA HONG KONG

Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019