


TT700P



Labels for Life.



Face Stock: 2 mil topcoated gloss white polyester offers excellent resistance to harsh chemicals and abrasion. The material is specifically designed to not shrink and for use on the top side of circuit boards where heat exposure is limited. The topcoat is UV flexographic and thermal transfer printable.

Adhesive: 0.8-0.9 mil high performance acrylic adhesive offering excellent chemical and abrasion resistance.

Release Liner: Available in 3.1 mil kraft, 1.5 mil polyester, or 3 mil glassine liner that offer excellent performance for applications where the label is applied manually.

Thermal Transfer Gloss White Polyester Film

TT700P is designed for UV flexographic printing with the option of additional on demand thermal transfer printing. Key features include: indoor and outdoor applications, will not shrink, anti-static properties, and excellent smudge, solvent, and abrasion resistance. When used in combination with the recommended IDENTCO inks and ribbons, it will meet the most demanding durable labeling requirements.

Typical Applications

- Name plates
- Rating Plates
- Serial identification labels
- Industrial Barcodes
- Electronic Components Marking

Typical Industry Sectors

- Automotive
- Electronics
- Industrial



www.identco.com

TT700P

Thermal Transfer Gloss White Film



Labels for Life.

Agency Recognitions

UL-MH16873/MH16225
CUL-MH16873/MH16225

Adhesion

Stainless Steel 55 oz/in	605 N/m	Polypropylene 15 oz/in	165 N/m
Polycarbonate 77 oz/in	847 N/m		

Material Caliper

Face Stock	.0020"	50.8μ	Liner (kraft/FL)	.0031"	78.7μ
Adhesive	.0008"/.0009"	20.3/22.9μ	Total Material	.0059"/.0060"	149.9/152.4μ

Exterior Durability

Material Only: 2 Years
Material w/ TTRR-D Ribbon: 2 Years

Temperature Range

Service Temperature: -40°F to 300°F (-40°C to 149°C)
Minimum Application Temperature: 50°F (10°C)

Shelf Life

Recommended Storage: 45-90°F (7-32°C) 20-75% R.H.
Shelf Life: 2 years @ recommended storage

Recommended Ribbons

TTRR-B TTRR-D
TTRR-V

Chemical Resistance

Chemical Agents	Material Only (w/o printing)	Printing (TTRR-D Ribbon)	Printing (Cotton swab rub)
Household Cleaners	Passed	Passed	Passed
Oil	Passed	Passed	Passed
Water	Passed	Passed	Passed
Isopropyl Alcohol	Passed	Passed	Passed
Mild Acid	Passed	Passed	Passed
Mineral Spirits	Passed	Passed	Passed
Toluene	Passed	Failed	Failed

Process Durability

It is recommended that customers test the material in actual application to determine if the material meets all requirements.

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 11/1/2016

UNITED STATES HEADQUARTERS
28164 W. Concrete Drive
Ingleside, IL 60041
Phone: +1 (815) 385 - 0011
Fax +1 (815) 385 - 0359

MEXICO MONTERREY
Carr. a Laredo Km. 16.5 Interior
14B, Col. Moisés Sáenz, 66613
Apodaca, Nuevo Leon
Phone: +52 (81) 8008 - 0438

GERMANY FRANKFURT
Güterbahnhofstrasse 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

PRC HONG KONG
Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019

MALAYSIA PENANG
Suite 163E, Level 16, Room 1602
Hunza Tower Gurney Paragon
Jalan Kelawai, Georgetown
10250 Penang
Phone: +6012 466 - 0866