


TT760P



Labels for Life.



Face Stock: 2 mil topcoated gloss white polyester offers excellent resistance to smudges, solvents and abrasion. The material is specifically designed for use on the top side of printed circuit boards and to be UV flexographic printed. The material will not shrink.

Adhesive: 1.9-2.1 mil high performance, heavy duty permanent acrylic adhesive offering excellent solvent, smudge and abrasion resistance. Specifically designed for smooth, but difficult to adhere to surfaces.

Release Liner: 50# kraft liner designed to offer excellent performance for manual application.

Thermal Transfer Gloss White Polyester Film

TT760P is designed for on demand and UV flexographic printing of variable information. Key features include: indoor and outdoor applications, will not shrink and excellent chemical, smudge and abrasion resistance. When used in combination with the recommended IDENTCO ribbon, it will meet the most demanding durable labeling requirements. Preheating of the label surface will enhance the performance.

Typical Applications

- Name plates
- Rating plates
- Industrial Barcodes
- Property Identification
- Serial Identification
- Electronic components marking

Typical Industry Sectors

- Automotive
- Electronics
- Industrial



www.identco.com


TT760P

Thermal Transfer Gloss White Polyester Film




Labels for Life.


 **Agency Recognitions**
UL-MH16873/ MH16225
RoHS Directive Compliant 2002/95/EC


 **Adhesion**


Stainless Steel	87 oz/in	957 N/m	HD Polypropylene	42 oz/in	462 N/m
Acrylic Power Paint	89 oz/in	979 N/m	Polycarbonate	99 oz/in	1089 N/m
Polypropylene	36 oz/in	396 N/m	Epoxy Power Paint	111 oz/in	1221 N/m
			Polyester Powder Paint	47 oz/in	517 N/m


 **Material Caliper**
Face Stock .0020" 50.8μ
Adhesive .0019"/.0021" 48.2/53.3μ
Liner(kraft) .0030" 76.2μ
Total Material .0069"/.0071" 175.2/180.3μ

 **Exterior Durability**
Material Only: 2 Years
Material w/ TTRR-D Ribbon: 2 Years

 **Temperature Range**
Service Temperature: -40 °F to 302 °F (-40 °C to 150 °C)
Minimum Application Temperature: 50 °F (10 °C)

 **Shelf Life**
Recommended Storage: 45-90 °F (7-32 °C) 20-75% R.H.
Shelf Life: 2 years @ recommended storage

 **Recommended Ribbons**
TTRR-B UL
TTRR-D UL

 **Process Durability**
It is recommended that customers test the material in actual application to determine if the material meets all requirements.

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 8/2/2017.

UNITED STATES HEADQUARTERS

28164 W. Concrete Drive
Ingleside, IL 60041
Phone: +1 (815) 385 - 0011
Fax +1 (815) 385 - 0359

MEXICO MONTERREY

Carr. a Laredo Km. 16.5 Interior
14B, Col. Moisés Sáenz, 66613
Apodaca, Nuevo Leon
Phone: +52 (81) 8008 - 0438

GERMANY FRANKFURT

Güterbahnhofstrasse 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

PRC HONG KONG

Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019

MALAYSIA PENANG

Suite 163E, Level 16, Room 1602
Hunza Tower Gurney Paragon
Jalan Kelawei, Georgetown
10250 Penang
Phone: +6012 466 - 0866