

ELP™ - I



Labels for Life.



Two configurations with interchangeable print heads

300dpi • 600dpi

Standard Interfaces

- USB 2.0
- Ethernet
- Parallel
- 9-pin RS-232
- 2 USB hosts for scanner or keyboard

Stand Alone Printing

Stand Alone Mode promotes cost savings by ease of use, freeing up valuable floor space and allowing diverse printer placement. No PC needed.

Available to quote today!
sales@identco.com
1 (800) 533-2559

Highlights

- Interchangeable printheads
- 1 printer = 2 printers (300-600dpi)
- Exceptional print registration
- Print with web widths as narrow as .45"
- Center align version
- Large color LCD touch screen
- Minimal waste during calibration
- Easy loading and removal of labels/ribbons
- Very user friendly operation

Features

- 450 meter ribbon lengths
- 6" per second print speed at 600dpi
- Holds 8" OD media rolls
- Standard 1" core ribbons, CSO/CSI
- 2 year printer warranty
- Optional Cutter
- Optional Applicator



www.identco.com



Labels for Life.

● G5B85F8 ○ CDHCB

| | | 9@d! | |
|---------------------|---|----------|----------|
| | | ' \$\$\$ | * \$\$\$ |
| Printhead | Df]bha Yh.cX' | TT/DT | TT/DT |
| | Df]bhfygc'i h]cb'Xd] | ' \$\$\$ | * \$\$\$ |
| | Df]bh'gdYYX'i d'hc'a a #g' | 30\$ | %\$ |
| | Df]bhk]Xh'a a' | %) "" | %) "" |
| A UHyf]U' | A YX]U'fc""hcU'X]Ua YHyf'i d'hc'a a' | &\$) | &\$) |
| | @UVY'k]Xh'a a' | (' %\$) | (' %\$) |
| | @UVY'\Y][\hk]h'ci hZYXVUW'Z'ca'a a' | (| (|
| | @UVY'\Y][\hi d'hc'a a' | (\$\$\$ | %)\$\$\$ |
| F]VWcb | b_' | CSO/CSI | CSO/CSI |
| | F]VWcb"Yb[h'j Uf]UV'Y'i d'hc'a a' |) \$\$ |) \$\$ |
| Df]bhYf'8]a Ybg]cbg | <Y][\hi'XYdh'a a' | &+(I((* | &+(I((* |
| | K]Xh'a a' | &(& | &(& |
| 9YVWcb]Vg | DfcWggcf'\][\gdYYX'WcW'fUH'A <n' | &** | &** |
| | F5A 'A 6' | * (| * (|
| | A Ya cfm::G'A 6:'Ug\' | , | , |
| | G'chZcf'7ca dUW'h:'Ug\ 'A Ya cfm7UfX | ● | ● |
| | G'chZcf'k]fY'Ygg:@5B'WfX' | ● | ● |
| | 6UH'Yfm6i ZYf'7UfX, Real-time clock, Printout of time and date, Data storage on shut down | | |
| | K Ufb]b['g][bU'/acoustic signal in case of error' | | |
| bhYfZUWg | 7Ybhfc]Vg]V]!X]fYV]cbU'UWV'999'&, (' | ○ | ○ |
| | FG&' &7' | ● | ● |
| | I G6'&"\$<][\ 'GdYYX'G'Uj Y'Zcf'D7' | ● | ● |
| | 9h YfbYh%\$#%\$ \$6Ugy H' | ● | ● |
| | FG(&&ZFG(,)' | ○ | ○ |
| | DYf]d\YfU'W'bbYV]cb' | ● | ● |
| | K @5B'WfX', \$&%%6V#' | ○ | ○ |
| | &l 'I G6'A UghYf'Zcf'YI hYfU'cdYfU]cb'dUbY'žgWbbYfz'_YnVcUfXžgyfj]W'_Ym | | |
| 7YbhYf'5']bYX' | CfXYf WbhYf!U][bYXj Yfg]cb'Zcf'k YV'k]Xh.gO%\$" | | |

89BH7C'cZyfg'h.Y 9@d 'gyf]Yg'cZh Yfa U'hfUbgZyf'df]bhYfg": UghYf'9@d 'df]bhYfg'U'ck'i gyfg'hc'cUXž
df]bhžUbX'W.Ub[Y'a UHyf]U'g'a cFY'YZ]VYbhmi'H.Y'UV']]mhc'cdYfU]cb'k]h 'U'W'a di hYf'cf'bYhk cf'_cf'jb'
ghUbX!U'cbY'a cXY'cZyfg'ZYI]V'Y'df]bhYf'cdYfU]cb"

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 7/7/2017.

UNITED STATES HEADQUARTERS
28164 W. Concrete Drive
Ingleside, IL 60041
Phone: +1 (815) 385 - 0011
Fax +1 (815) 385 - 0359

MEXICO MONTERREY
Carr. a Laredo Km. 16.5 Interior
14B, Col. Moisés Sáenz, 66613
Apodaca, Nuevo Leon
Phone: +52 (81) 8008 - 0438

GERMANY FRANKFURT
Güterbahnhofstrasse 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

PRC HONG KONG
Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019

MALAYSIA PENANG
Suite 163E, Level 16, Room 1602
Hunza Tower Gurney Paragon
Jalan Kelawei, Georgetown
10250 Penang
Phone: +6012 466 - 0866