


TT602



Labels for Life.



Face Stock: 3 mil topcoated matte white biaxially oriented polypropylene offers excellent resistance to harsh chemicals, moisture and abrasion. The material is ideal for marking electronic components where the heat requirement of polyester is not required.

Adhesive: 0.8 mil high performance emulsion acrylic adhesive offering high initial tack and excellent chemical and abrasion resistance.

Release Liner: 50# kraft liner designed to offer excellent performance for automatic application.

Thermal Transfer Matte White Biaxially Oriented Polypropylene Film

TT602 is designed for on demand thermal transfer printing of variable information. Key features include: indoor only applications and excellent smudge, moisture, solvent and abrasion resistance. When used in combination with the recommended IDENTCO ribbon, it will meet the most demanding durable labeling requirements. Preheating of the label surface will enhance the performance. This material is an excellent choice for automatic application.

Typical Applications

- Electronic Component Marking
- Rating Plates
- Nameplates
- Boxes
- Industrial Barcodes

Typical Industry Sectors

- Automotive
- Electronics
- Industrial



identco.com

TT602

Thermal Transfer Matte White
Biaxially Oriented Polypropylene Film



Labels for Life.

	Agency Recognitions UL-MH16873/MH16225													
	Adhesion Peel adhesion measured at 180 degrees Stainless Steel 59.6 oz/ in 655 N/m	Aluminum 60 oz/in 660 N/m ABS 62.9 oz/ in 691.9 N/m Polypropylene 5.4 oz/in 59.4 N/m												
	Material Caliper Face Stock .0030" 76.2μ Adhesive .0008" 20.3μ	Liner(kraft) .0032" 81.3μ Total Material .0070" 177.8μ												
	Exterior Durability Recommended: Indoor use only.													
	Temperature Range Service Temperature: -40°F to 176°F (-40°C to 80°C) Minimum Application Temperature: 50°F (10°C)													
	Shelf Life Recommended Storage: 45-90°F (7-32°C) 20-75% R.H. Shelf Life: 2 years @ recommended storage													
	Recommended Ribbons TTRR-A TTR TTRR-B TTRR-D													
	Chemical Resistance Chemical Agents	<table border="1"><thead><tr><th>Material Only (W/o printing)</th><th>Printing (TTRR Ribbon)</th><th>Printing (Cotton swab rub)</th></tr></thead><tbody><tr><td>Household Cleaners Passed</td><td>Passed</td><td>Passed</td></tr><tr><td>Water Passed</td><td>Passed</td><td>Passed</td></tr><tr><td>Isopropyl Alcohol Passed</td><td>Passed</td><td>Passed</td></tr></tbody></table>	Material Only (W/o printing)	Printing (TTRR Ribbon)	Printing (Cotton swab rub)	Household Cleaners Passed	Passed	Passed	Water Passed	Passed	Passed	Isopropyl Alcohol Passed	Passed	Passed
Material Only (W/o printing)	Printing (TTRR Ribbon)	Printing (Cotton swab rub)												
Household Cleaners Passed	Passed	Passed												
Water Passed	Passed	Passed												
Isopropyl Alcohol Passed	Passed	Passed												
	Process Durability It is recommended that customers test the material in actual application to determine if the material meets all requirements.													

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 11/1/2016

UNITED STATES HEADQUARTERS

28164 W. Concrete Drive,
Ingleside, IL 60041 USA
Phone: +1 (815) 385 - 0011
Fax + (815) 385 - 0359

MEXICO MONTERREY

Carretera a Laredo KM 16.5
Bodega 14B Colonia Moisés Sáenz
Apodaca, Nuevo León CP 66613
Phone: +52 (81) 8008 - 0438

EUROPE GERMANY

Güterbahnhofstraße 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

ASIA PRC

Unit 1208, 12/F, Grand City Plaza
No.1-17 Sai Lau Kok Road
Tsuen Wan, New Territories, Hong Kong
Phone: +852 2959 2156 • Fax: +852 2959 2019